

Product Specifications

| Category | Feature | Specification |
|------------|------------------------------|--|
| General | CPU | 1.4GHz Octa-core |
| | Memory | 8GB Flash + 1GB RAM |
| | LED | Multi-color <ul style="list-style-type: none"> • STATUS - 2ea • HOST RS-485 TX - 1ea • HOST RS-485 RX - 1ea • SUPERVISED INPUT - 8ea • RELAY - 2ea • AUX IN - 2ea |
| | Operating temperature | 0°C ~ 50°C |
| | Storage temperature | -40°C ~ 70°C |
| | Operating humidity | 0% ~ 80%, non-condensing |
| | Storage humidity | 0% ~ 95%, non-condensing |
| | Dimension (W x H x D) | 150 mm x 214 mm x 21 mm |
| | Weight | 415 g |
| | Certificates | CE, FCC, KC, RoHS, REACH, WEEE |
| Capacity | Max. User (1:1) | 500,000 |
| | Max. User (1:N) | 100,000 |
| | Max. Template (1:1) | 1,000,000 (Two templates per finger) |
| | Max. Template (1:N) | 200,000 (Two templates per finger) |
| | Max. RF Card | 500,000 |
| | Max. PIN | 500,000 |
| | Max. Text Log | 5,000,000 |
| Interface | Ethernet | 10/100 Mbps, 자동 MDI/MDI-X |
| | RS-485 | 5ch |
| | Wiegand | 4ch |
| | Supervised Input | 8ch (TTL input selectable) |
| | TTL Output | 8ch |
| | AUX Input | 2ch (AC POWER FAIL, Tamper) |
| Electrical | Power | <ul style="list-style-type: none"> • CoreStation <ul style="list-style-type: none"> - Voltage: 12VDC, Current: Max. 3A • Power Supply (SMPS) AC INPUT <ul style="list-style-type: none"> - 110-240VAC, 50/60Hz |
| | Power Output | Voltage: 12VDC Current: Max. 1.5A |
| | Switch input V _{IH} | Max.: 5V Min.: 4V |
| | Switch input V _{IL} | Max. 1V |
| | Relay | Voltage: Max. 30VDC Current: Max. 5A |